


Signature Series®

Aluminum Clad Wood Windows & Doors


SIGNATURE SERIES - SIDE HINGED FRENCH DOOR 2-PANEL INSWING (HINGE CODE B) (8510)

SCALE: ELECTRONIC FILE IS FULL SCALE INTRODUCED 7/12 LAST UPDATE 1/29/13


- WEATHER SHIELD RESERVES THE RIGHT, AS NECESSARY, TO CHANGE PRODUCT SPECIFICATIONS AND MATERIALS WITHOUT NOTICE.
 DIMENSIONS MAY BE ROUNDED TO THE NEAREST 1/16" [2mm].
- IMPORTANT: DIMENSIONS SHOWN ARE FOR STANDARD SHIM SPACE BETWEEN JAMB AND ROUGH OPENING
- WHEN INSTALLING IN A JURISDICTION REQUIRING DESIGN PRESSURE (DP) RATED PERFORMANCE, WINDOW AND DOOR PRODUCTS MUST BE INSTALLED IN THE SAME METHOD THEY WERE INSTALLED FOR TESTING. A SHIM SPACE, NOT TO EXCEED 1/4" [6mm] IS REQUIRED AROUND THE SIDE JAMBS AND HEAD OF UNITS.
 • REFER TO INSTALLATION INSTRUCTIONS FOR COMPLETE DETAILS.
- FRENCH DOORS WITH THREE-POINT LOCK SYSTEM ARE MANUFACTURED WITH A SHOOTBOLT AND SHOOTBOLT GROMMET AT HEAD (SHOWN) WHICH PROTRUEDS THROUGH THE HEAD INTO ROUGH OPENING APPROXIMATELY 7/16" [11mm]



B - HORIZONTAL SECTION



C - VERTICAL 1-1/2" [38mm] **SPREAD MULL**



A - VERTICAL SECTION STANDARD SILL