EnduraShield Fiberglass Double Hung Windows - Wood Interiors
Opening Specifications

Call Size	Sq. Ft. Clear Opening	Clear Opening		Sq. Ft. Daylight Opening	Sq. Ft. Vent	Floor to Bottom of Clear Opening[a]	Sq. Ft. Overall Unit Area[b]
		Width	Height				
1630	1.251	13.625	13.219	1.992	1.251	49.063	4.31
1636	1.535	13.625	16.219	2.435	1.535	43.063	5.04
1640	1.818	13.625	19.219	2.878	1.818	37.063	5.77
1646	2.102	13.625	22.219	3.320	2.102	31.063	6.50
1650	2.386	13.625	25.219	3.763	2.386	25.063	7.23
1656	2.670	13.625	28.219	4.206	2.670	19.063	7.96
1660	2.954	13.625	31.219	4.648	2.954	13.063	8.69
1666	3.238	13.625	34.219	5.091	3.238	7.063	9.42
2030	1.802	19.625	13.219	3.117	1.802	49.063	5.79
2036	2.210	19.625	16.219	3.810	2.210	43.063	6.77
2040	2.619	19.625	19.219	4.503	2.619	37.063	7.75
2046	3.028	19.625	22.219	5.195	3.028	31.063	8.73
2050	3.437	19.625	25.219	5.888	3.437	25.063	9.71
2056	3.846	19.625	28.219	6.581	3.846	19.063	10.69
2060	4.255	19.625	31.219	7.273	4.255	13.063	11.67
2066	4.663	19.625	34.219	7.966	4.663	7.063	12.65
2630	2.352	25.625	13.219	4.242	2.352	49.063	7.27
2636	2.886	25.625	16.219	5.185	2.886	43.063	8.50
2640	3.420	25.625	19.219	6.128	3.420	37.063	9.73
2646	3.954	25.625	22.219	7.070	3.954	31.063	10.96
2650	4.488	25.625	25.219	8.013	4.488	25.063	12.19
2656	5.022	25.625	28.219	8.956	5.022	19.063	13.42
2660	5.555	25.625	31.219	9.898	5.555	13.063	14.65
2666	6.089	25.625	34.219	10.841	6.089	7.063	15.88
2830	2.536	27.625	13.219	4.617	2.536	49.063	7.77
2836	3.111	27.625	16.219	5.643	3.111	43.063	9.08
2840	3.687	27.625	19.219	6.669	3.687	37.063	10.39
2846	4.262	27.625	22.219	7.695	4.262	31.063	11.70
2850	4.838	27.625	25.219	8.721	4.838	25.063	13.02
2856	5.413	27.625	28.219	9.747	5.413	19.063	14.33
2860	5.989	27.625	31.219	10.773	5.989	13.063	15.64
2866	6.565	27.625	34.219	11.799	6.565	7.063	16.95
3030	2.903	31.625	13.219	5.367	2.903	49.063	8.75
3036	3.562	31.625	16.219	6.560	3.562	43.063	10.23
3040	4.221	31.625	19.219	7.753	4.221	37.063	11.71
3046	4.880	31.625	22.219	8.945	4.880	31.063	13.19
3050	5.538	31.625	25.219	10.138	5.538	25.063	14.67
3056	6.197	31.625	28.219	11.331	6.197	19.063	16.15
3060	6.856	31.625	31.219	12.523	6.856	13.063	17.63
3066	7.515	31.625	34.219	13.716	7.515	7.063	19.11
3630	3.454	37.625	13.219	6.492	3.454	49.063	10.23
3636	4.238	37.625	16.219	7.935	4.238	43.063	11.96
3640	5.022	37.625	19.219	9.378	5.022	37.063	13.69
3646	5.805	37.625	22.219	10.820	5.805	31.063	15.42
3650	6.589	37.625	25.219	12.263	6.589	25.063	17.15
3656	7.373	37.625	28.219	13.706	7.373	19.063	18.88
3660	8.157	37.625	31.219	15.148	8.157	13.063	20.61
3666	8.941	37.625	34.219	16.591	8.941	7.063	22.34
4030	4.005	43.625	13.219	7.617	4.005	49.063	11.71
4036	4.913	43.625	16.219	9.310	4.913	43.063	13.69
4040	5.822	43.625	19.219	11.003	5.822	37.063	15.67
4046	6.731	43.625	22.219	12.695	6.731	31.063	17.65
4050	7.640	43.625	25.219	14.388	7.640	25.063	19.63
4056	8.549	43.625	28.219	16.081	8.549	19.063	21.61
4060	9.458	43.625	31.219	17.773	9.458	13.063	23.59
4066	10.367	43.625	34.219	19.466	10.367	7.063	25.56

Shaded sizes meet or exceed egress opening requirements per 2006 IBC (International Building Code) minimum dimensions of 20" clear opening width, 24" clear opening height, 5.7 sq. ft. clear opening and floor to bottom of clear opening not to exceed 44" in height. Verify local or state egress opening sizes with your local building inspector.

a - Floor to bottom of clear opening dimensions are based on 82" jamb height of a typical door.

b - Sq. Ft. Overall Unit Area is calculated on the jamb dimension.